

© EPODOC / EPO

PN - JP2002309157 A 20021023
PD - 2002-10-23
PR - JP20010118034 20010417
OPD - 2001-04-17
TI - INFRARED LIGHT-SHIELDING COATING FOR TRANSPARENT
BASE MATERIAL, AND COATING FILM-FORMING METHOD AND
TRANSPARENT BASE MATERIAL
IN - MIKI KATSUO;MIKI NOBUNORI;NOUE KOICHI
PA - NIPPON PAINT CO LTD;MIKI KATSUO
IC - C09D133/14 ; B05D1/28 ; B05D5/06 ; B05D7/24 ; B32B7/02 ;
B32B27/30 ; C09D5/33 ; C09D183/02 ; C09K3/00

© WPI / DERWENT

TI - IR rays shielding coating for transparent substrates contains resin
composition and tin-containing indium oxide coating layers
PR - JP20010118034 20010417
PN - JP2002309157 A 20021023 DW200313 C09D133/14 008pp
PA - (MIKI-I) MIKI K
- (NIPA) NIPPON PAINT CO LTD
IC - B05D1/28 ;B05D5/06 ;B05D7/24 ;B32B7/02 ;B32B27/30 ;C09D5/33
;C09D133/14 ;C09D183/02 ;C09K3/00
AB - JP2002309157 NOVELTY - A novel IR rays shielding coating
composition (P1) for transparent substrates contains a resin
composition (A) and tin-containing indium oxide (B) that has a
primary article diameter of 0.01-0.1 micron.
- DETAILED DESCRIPTION - A novel IR rays shielding coating
composition (P1) for transparent substrates contains a resin
composition (A) and tin-containing indium oxide (B) that has a
primary article diameter of 0.01-0.1 micron. (A) contains a hydroxyl
group-containing acrylic resin (A-1) that has a number average
molecular weight of 1,000-50,000 and a tetrafunctional silicon
compound of formula (I) and/or its condensed derivative (A2).
- R's = each 1-10C alkyl or alkoxyalkyl; and
- n = integer of 1-20.
- In (P1), (A) has an (A-1)/(A-2) solid weight ratio of 10/1-1/3 and an
(A)/(B) solid weight ratio of 100/0.5-100/20.
- INDEPENDENT CLAIM are also included for:
- (1) a novel formation (M) of coating layers that comprises a process
in which (P1) is coated on the surface of a transparent substrate;
and

- (2) a novel transparent substrate (P2) that has a coating layer formed by means of (M).
- USE - (P1) is suitable for surface coating transparent substrates like glass and plastics, such as window glasses of buildings and/or automobiles to impart IR rays shielding effect to them. (P2) is used for lowering the inside temperature of structures formed using it by shielding IR rays.
- ADVANTAGE - (P1) forms coating layers that exhibits excellent IR rays shielding effect and adhesion to various transparent substrates and high transmission ratio of visible light.
- (Dwg.0/2)

OPD - 2001-04-17

AN - 2003-132501 [13]

©PAJ/JPO

PN - JP2002309157 A 20021023

PD - 2002-10-23

AP - JP20010118034 20010417

IN - MIKI NOBUNORINOUE KOICHI MIKI KATSUO

PA - NIPPON PAINT CO LTD MIKI KATSUO

TI - INFRARED LIGHT-SHIELDING COATING FOR TRANSPARENT
BASE MATERIAL, AND COATING FILM-FORMING METHOD AND
TRANSPARENT BASE MATERIAL

- AB - PROBLEM TO BE SOLVED: To provide an infrared light-shielding coating for a transparent base material which gives a coating film having a high transmittance in the visible light region, excellent in infrared light-shielding properties and exhibiting excellent performances such as adhesion and the like.
- SOLUTION: The infrared light-shielding coating for a transparent base material comprises (A) a resin composition containing (A-1) an acrylic resin bearing a hydroxy group with a number-average molecular weight of 1,000-50,000 and (A-2) a tetrafunctional silicon compound represented by the general formula (1) (wherein R is the same of different from each other and is a 1-10C alkyl or alkoxyalkyl group; and n is an integer of 1-20) and/or a condensate thereof, and (B) a tin-containing indium oxide having a primary particle size of 0.01-0.1 μm , where the solid content weight ratio of (A-1) the acrylic resin to (A-2) the tetrafunctional silicon compound and/or a condensate thereof is 10/1-1/3 and the solid content weight ratio of (A) the resin composition to (B) the tin-containing indium oxide is 100/0.5-100/20.

I - C09D133/14 ;B05D1/28 ;B05D5/06 ;B05D7/24 ;B32B7/02

;B32B27/30 ;C09D5/33 ;C09D183/02 ;C09K3/00